

F10 Series



Standard Technical Data

Output type	3-wire
Switching function	Normally-open (NO)
Voltage type	DC
Switching frequency	500 Hz
Operating voltage (min)	10 V
Operating voltage (max)	30 V
Housing length L	38.5 mm
Housing width W	25 mm
Housing height H	25.5 mm
UL	■

For detailed data and description, see the datasheet. Further products can be found online at www.pepperl-fuchs.com.

Model number	Type of installation	Detection range [mm]	Output type	Connection type	Cable length [mm]	Cable material	EAC
NBB7-F10-E0	Flush	7	NPN	Fixed cable	2000	PVC	
NBB7-F10-E2	Flush	7	PNP	Fixed cable	2000	PVC	
NBN10-F10-E0	Non-flush	10	NPN	Fixed cable	2000	PVC	
NBN10-F10-E0-V1	Non-flush	10	NPN	M12 connector plug			
NBN10-F10-E2	Non-flush	10	PNP	Fixed cable	2000	PVC	■
NBN10-F10-E2-V1	Non-flush	10	PNP	M12 connector plug			

Accessories

V1-G-2M-PUR	Single-ended female cordset, M12, 4-pin, PUR cable
V1-W-2M-PUR	Single-ended female cordset, M12, 4-pin, PUR cable

