



M11 Series



Standard Technical Data	
Output type	2-wire
Output type	NAMUR
Switching function	Normally-closed (NC)
Voltage type	DC
Switching frequency	3000 Hz
Operating voltage (min)	8.2 V
Operating voltage (max)	8.2 V
Connection type	Fixed cable
Cable material	PVC
ATEX	■
UL	■

For detailed data and description, see the datasheet. Further products can be found online at www.pepperl-fuchs.com.

Model number	Type of installation	Detection range [mm]	SIL	Cable length [mm]	Length L	Diameter D	EAC	FM
NJ2-11-N	Flush	2	2	2000	31	11	■	■
NJ2-11-N-G	Flush	2	2	2000	30	14	■	■
NJ2-11-N-G-5M	Flush	2	2	5000	30	14	■	■
NJ2-11-N-G-10M	Flush	2		10000	30	14	■	
NJ5-11-N-G	Non-flush	5	2	2000	31	14	■	
NJ5-11-N-G-5M	Non-flush	5	2	5000	31	14	■	
NJ5-11-N-G-10M	Non-flush	5	2	10000	31	14	■	
NJ5-11-N-G-6M	Non-flush	5	2	6000	31	14	■	

Accessories	
BF 11	Mounting adapter, 11 mm

