



Ring Diameter 15 mm



| Standard Technical Data | |
|-------------------------|----------------------|
| Special features | Ex sensor |
| Detection range | 15 mm |
| Output type | 2-wire |
| Output type | NAMUR |
| Switching function | Normally-closed (NC) |
| Voltage type | DC |
| Operating voltage (min) | 8.2 V |
| Operating voltage (max) | 8.2 V |
| Connection type | Fixed cable |
| Cable material | PVC |
| ATEX | ■ |
| CSA | ■ |
| UL | ■ |

For detailed data and description, see the datasheet. Further products can be found online at www.pepperl-fuchs.com.

| Model number | Switching frequency [Hz] | Cable length [mm] | Ambient temperature (min) | Ambient temperature (max) | Length L | Width W | Height H | FM | ATEX |
|--------------|--------------------------|-------------------|---------------------------|---------------------------|----------|---------|----------|----|------|
| RC15-14-N0 | 1500 | 2000 | -20 | 65 | 20 | 25 | 32.5 | ■ | ■ |
| RC15-14-N3 | | 2000 | -20 | 70 | 20 | 25 | 32.5 | ■ | ■ |
| RJ15-14-N | 1500 | 2000 | -25 | 70 | 20 | 25 | 32.5 | | |
| RJ15-14-N-5M | 1500 | 5000 | -25 | 70 | 20 | 25 | 32.5 | | |
| RJ15-N | 1500 | 2000 | -25 | 70 | 25 | 29 | 45 | ■ | |

